

TECHNICAL DATA SHEET

28/11/13

REF: AS216SH - Standard Cloth Tape

DESCRIP: A synthetic rubber based cloth tape with a waterproof PE Polyethylene synthetic coated fabric which is tearable by hand. Cloth tape has a strong initial tack and a good adhesive power.

SPEC:	<u>Width:</u>	48, 50, 72 mm & others upon request
	<u>Length of Rolls:</u>	50M & others upon request
	<u>Core:</u>	76mm
	<u>Adhesive</u>	Hotmelt/synthetic rubber
	<u>Carrier</u>	PE coated fabric
	<u>Thickness</u>	150 µm
	<u>Mesh density (fabric)</u>	18
	<u>Adhesion on steel</u>	17.5 (N/25mm)
	<u>Rolling ball tack</u>	<3 cm
	<u>Tensile strength</u>	70 N/25mm)
	<u>Service temperature</u>	-10 up to +75 °C

STORAGE Store in a cool dry place away from sunlight and direct heat sources. As far as the storage conditions are respected, the product is guaranteed 12 months.

USES: Ideal for adhesion on smooth and rough surfaces such as stainless steel, polyethylene, glass and wood and is used for general application such as repairing, sealing holding, protecting and bundling. Also widely used for sealing applications in the thermal insulation and construction industries. Widely used for sealing asbestos removal enclosures.

APPLICATION: Prior to use carefully check that the contact surfaces are totally dry and clean from all traces of oil, grease and dust.

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to satisfy himself at all times as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.