



Adhesive Specialities Ltd
Tickitape House, 31 Bone Lane
Newbury, RG14 5SH
+44(0)1635 49825

TECHNICAL DATA SHEET

26/11/13

REF: AS329BA Double Sided Carpet Tape

DESCRIP: Double-sided self-adhesive tape with polypropylene carrier, white synthetic rubber adhesive.

FEATURES: Adhesive with balanced features for tack, adhesion and cohesion.

SPEC:	<u>Width:</u>	50mm
	<u>Length:</u>	50m
	<u>Core Size:</u>	76mm
	<u>Liner:</u>	80 g yellow two side siliconised paper
	<u>Carrier:</u>	Clear cast PP
	<u>Adhesive:</u>	White synthetic rubber
	<u>Thickness</u>	155 µm
	<u>Liner Thickness:</u>	70 µm
	<u>Tensile Strength:</u>	21 N/cm
	<u>Peel 180°:</u>	8 N/cm
	<u>Elongation at Break:</u>	490%
	<u>Static Shear</u>	>30 h
	<u>Rolling Ball Tack:</u>	<3 cm
	<u>Service temperature</u>	10° C to + 30° C
	<u>Performing temperature</u>	-10° C to + 50° C
	<u>Short passage temperature</u>	-20° C to + 50° C

STORAGE: When stored in the original packaging at 21°C and at 50% relative humidity the product has a shelf life of 12 months.

USES: This products high tack and good conformability make it suitable for carpet laying and other resilient flooring applications, also suitable for bonding plastic profiles and assembling rubber stamps.

APPLICATION: Prior to use carefully check that the contact surfaces are totally dry and clean from all traces of oil, grease and dust.

Above mentioned values represent the average values determined by standard test methods and as such they are not binding. Any recommendations stated by the Company are made in good faith but cannot over-ride the basic obligation of the User to satisfy himself at all times as to suitability of the widely varying environmental conditions, the standards of application, and the changes in technology which can alter the properties of materials with which our products are expected to perform.